

HYOSUNG MV400

Easy, fast and secure card issuance machine MoniValue400 provides operational efficiency and better customer experience.

MV400 is an intelligent and powerful card issuing kiosk, delivering a fast, secure and personalized card issuing service. MV400 offers proven reliability, easy operation and less maintenance.

Features

IMPROVED PRODUCTIVITY IN BRANCH

The reliable and powerful MoniValue400 enables maximum branch productivity by shortening the customer queue for card issuance while reducing costs.

MINIMUM MAINTENANCE NEEDS

Greater serviceability in system configuration makes diagnosis and repair easy; and high reliability lowers maintenance needs and costs.

HIGHER CUSTOMER SATISFACTION

Versatile printing (e.g. monochrome or full colored, dual-side) satisfies diverse customer preferences. It personalizes customer service with the edge-to-edge card issuance.





HYOSUNG MV400

Specifications

System Platform

- Microsoft Windows 10
- Hyosung Moniplus™ XFS

Customer Interface

- 21.5 inch display
- Lead-through Indicator
- PIN Pad PCI compliant
- Card Reader EMV Ready (Dip, Motorized)
- Contactless card reader (Integrated NFC reader via card, smartphone or smartwatch)
- Audio speaker / earphone jack

Printer

- Receipt printer : graphical thermal printer
- Journal printer : e-Journal (Thermal printer optional)

Media Technology

• Card Dispenser

- Hyosung Moniplus™ XFS
- Motorized card issuance
- Dual-side print (optional)
- EMV compliant, RF Read / Write
- 8 Hoppers x 100ea (70ea Embossed)

Cash Acceptor (optional)

- 600 / 1,200 notes capacity cashbox
- Single Acceptor

Security

- Safe : UL291 Level 1
- Lock : Electronic lock, Mechanical combination lock
- Sensor : Alarm (Heat & Seismic), Door sensor
- Privacy filter
- Anti skimming, Anti card trapping, Anti shimming, Anti cash trapping
- Security camera (Face & Hand)
- MoniGuard endpoint security software

Additional Features

- Barcode reader
- Fingerprint reader
- Document scanner
- Document printer
- ID scanner
- Sign Pad

Power Supply

- AC 110 ~ 240V, 50 ~ 60Hz
- Backup battery

Environmental Conditions

- Temperature : 0°C ~ 40°C (32°F ~ 104°F)
- Humidity : 25% ~ 85%

Dimensions

- Height : 1,416mm (55.8 inch)
- Width : 625mm (24.6 inch)
- Depth : 798.3mm (31.4 inch)
- Weight : 300kg (661.39 lbs.)



(*) Internal Components may change with introduction of new technology. Hyosung TNS reserves the right to change the specifications of this ATM to accommodate the changes in technology.