

# Hyosung MX5600

INTERIOR FREESTANDING CASH DISPENSER

A robust, secure, and high-capacity solution.

The MX5600 allows complete deployment flexibility and a broad range of non-traditional offerings. The MX5600 is ideal for in-branch or off-premise deployments, and offers the best in class solution when high availability, security, and high capacity are required.

## Features

### HIGHEST AVAILABILITY

The MX5600 is designed to provide exceptional reliability, unequalled in the market with minimum maintenance and maximum uptime.

### FLEXIBILITY

Designed with an open architecture platform, the MX5600 allows for easy future upgrades and module modifications. The modular design and compact footprint are designed to save our customers cost and provide maximum convenience. A full range of advertising and marketing support is available with the MX5600.

### CAPACITY

The MX5600 has high capacity, high cash dispense capability, and the ability to support large volume transactions.

### SECURITY OPTIONS

Hyosung ATMs defend against physical and logical with a combination of multi-level anti-skimming, locked down operating system, white-listing, and encryption. The MX5600 is also easily integrated with any monitoring solutions to provide seamless data transfer for effective management of the self-service channels.





# Hyosung MX5600

INTERIOR FREESTANDING CASH DISPENSER

## Specifications

### Dimensions (CEN-I base)

- Height: 1508mm (59.3")
- Width: 467mm (18.2")
- Depth: 799mm (31.9")
- Weight: 443kg (978lbs)

### Environmental Conditions

- Temperature: 32°F - 104°F (0°C ~ 40°C)
- With Heater: -24°F - 104°F (-31°C ~ 40°C)
- Humidity 25% - 85%

### System Platform

- Microsoft Windows® 10

### Customer Interface

- 15" TFT LCD touch screen
- PIN Pad - PCI complaint
- ADA audio guidance - earphone jack
- Card Reader - DIP, EMV compliant
- Contactless - Integrated reader (via card, smartphone or smartwatch)

### Media Handling

- Cash Dispenser
  - 3,000 notes per cassette
  - Configurable denominations
  - Up to 5 high capacity dispense cassettes
  - Bundle present/retract
  - Note by note rejection
  - Automatic shutter

### Security

- Safe - UL291 level 1
- Alarm - Seismic + Heat
- Locking Device - Electronic safe lock, KABA Mas Cencon
- Sensor - Safety door sensor
- Security - Terminal block for easy security connections
- Security camera

### Printer

- 3.1" graphical thermal receipt printer

### Servicing

- Front Access
- State of health indicators for all modules

### Power Supply

- AC 100V ~ 127V±10%, 200V ~ 240V±10% 50/60Hz

### Additional Features

- Communication - TCP/IP

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.